



webref. SU5021B1



webref. SUM11A11

DYNAMIC LIGHT

ETAP luminaires

Including lamps

RECESSED LUMINAIRES

table explanation p 221

	module	lamp type	L x W x H mm	plan N.	air cm ²	order code
U5						
Square						
Standard reflector – satin-anodised aluminium – EQUILUM® baffles						
T5 - ø 16mm (3000K + 6500K)						
65°	600	3 + 3 x 14W	596 x 596 x 96	105	78	U5861/614DD
		3 + 3 x 14W	596 x 596 x 96	105		U5862/614DD
	625	3 + 3 x 14W	625 x 625 x 96	105		U5867/614DD

Options and accessories p. 12

Linear

Standard reflector – satin-anodised aluminium – EQUILUM® baffles						
T5 - ø 16mm (3000K + 6500K)						
65°	-	1 + 1 x 49W	1496 x 175 x 96	147	125	U5860/249DD
		1 + 1 x 49W	1496 x 189 x 96	148		U5866/249DD
		1 + 1 x 54W	1196 x 175 x 96	147		U5860/254DD
		1 + 1 x 54W	1196 x 296 x 96	148		U5866/254DD
	300	1 + 1 x 54W	1196 x 296 x 96	149		U5861/254DD
	625	1 + 1 x 54W	1246 x 308 x 96	149		U5867/254DD
	1800	1 + 1 x 49W	1720 x 196 x 96	151	125	U5865/249DD

Options and accessories p. 12

UM1

Square

Diffuser – acrylic / MesoOptics™ film

T5 - ø 16mm (3000K + 6500K)						
	600	2 + 2 x 24 W	596 x 596 x 110	109		UM101/424DD
	625	2 + 2 x 24W	625 x 625 x 110	109		UM107/424DD

Diffuser – polycarbonate / MesoOptics™ film

T5 - ø 16mm (3000K + 6500K)						
	600	2 + 2 x 24 W	596 x 596 x 110	109		UM101/424DDT0
	625	2 + 2 x 24W	625 x 625 x 110	109		UM107/424DDT0

Diffuser – acrylic / MesoOptics™ film

T5 - ø 16mm (3000K + 6500K)						
	600	2 + 2 x 24 W	596 x 596 x 110	109		UM111/424DD
	625	2 + 2 x 24W	625 x 625 x 110	109		UM117/424DD

Diffuser – polycarbonate / MesoOptics™ film

T5 - ø 16mm (3000K + 6500K)						
	600	2 + 2 x 24 W	596 x 596 x 110	109		UM111/424DDT0
	625	2 + 2 x 24W	625 x 625 x 110	109		UM117/424DDT0

Options and accessories p. 17


LIGHT CONTROLS



DYNAMIC LIGHT

RECESSED LUMINAIRES

table explanation p 221

module	lamp type	L x W x H mm	plan N.	air cm ²	order code
Linear					
Diffuser - acrylic / MesoOptics™ film					
	T5 - ø 16mm (3000K + 6500K)				
300	2 x 28W + 1 x 54W	1196 x 296 x 93	153		UM101/228DD
625	2 x 28W + 1 x 54W	1246 x 308 x 93	153		UM107/228DD
Diffuser - polycarbonate / MesoOptics™ film					
	T5 - ø 16mm (3000K + 6500K)				
300	2 x 28W + 1 x 54W	1196 x 296 x 93	153		UM101/228DDT0
625	2 x 28W + 1 x 54W	1246 x 308 x 93	153		UM107/228DDT0
Diffuser - acrylic / MesoOptics™ film					
	T5 - ø 16mm (3000K + 6500K)				
300	2 x 28W + 1 x 54W	1196 x 296 x 93	153		UM111/228DD
625	2 x 28W + 1 x 54W	1246 x 308 x 93	153		UM117/228DD
Diffuser - polycarbonate / MesoOptics™ film					
	T5 - ø 16mm (3000K + 6500K)				
300	2 x 28W + 1 x 54W	1196 x 296 x 93	153		UM111/228DDT0
625	2 x 28W + 1 x 54W	1246 x 308 x 93	153		UM117/228DDT0

Options and accessories p. 47

DALLE

Diffuser - glass / polycarbonate					
	T5 - ø 16mm (3000K + 6500K)				
600	4 + 4 x 14W	595 x 595 x 120	114		DALLE600-814BC/BFDALI
Diffuser - glass / polycarbonate					
	T5 - ø 16mm (RGB)				
600	3 + 3 + 3 x 14W	595 x 595 x 120	114		DALLE600-914RVBDALI

Options and accessories p. 23



webref. SR4013E5



webref. SR4013D1

DYNAMIC LIGHT

SURFACE MOUNTED AND SUSPENDED LUMINAIRES

table explanation p 221

	lamp type	L x W x H mm	plan N.	order code ¹	L x W x H mm	plan N.	order code ¹
R4							
Surface mounted luminaires – individual							
Standard reflector – satin-anodised aluminium – EQUILUM® baffles							
	T5 – ø 16mm (3000K + 6500K)						
65°	1 + 1 x 49W	1577 x 190 x 60	221	R4860/249DD	3057 x 190 x 60	222	R48601/249DD
	1 + 1 x 54W	1277 x 190 x 60	221	R4860/254DD	2457 x 190 x 60	222	R48601/254DD
Options and accessories p. 83							
Surface mounted luminaires – straight line mounting							
through wiring (5 x 1,5 mm ²): included as standard							
Standard reflector – satin-anodised aluminium – EQUILUM® baffles							
	T5 – ø 16mm (3000K + 6500K)						
65°	1 + 1 x 49W	1529 x 190 x 60	223	R4862/249DD	1480 x 190 x 60	223	R4864/249DD
	1 + 1 x 54W	1229 x 190 x 60	223	R4862/254DD	1180 x 190 x 60	223	R4864/254DD
Options and accessories p. 83							
Surface mounted luminaires – angular line mounting							
through wiring (5 x 1,5 mm ²): included as standard							
Standard reflector – satin-anodised aluminium – EQUILUM® baffles							
	T5 – ø 16mm (3000K + 6500K)						
65°	1 + 1 x 49W	1529 x 190 x 60	224	R4866/249DD	1480 x 190 x 60	224	R4868/249DD
	1 + 1 x 54W	1229 x 190 x 60	224	R4866/254DD	1180 x 190 x 60	224	R4868/254DD
Options and accessories p. 83							
Suspended luminaires – individual							
Standard reflector – satin-anodised aluminium – EQUILUM® baffles							
	T5 – ø 16mm (3000K + 6500K)						
65°	1 + 1 x 49W	1577 x 190 x 60	225	R4861/249DD	3057 x 190 x 60	226	R48611/249DD
	1 + 1 x 54W	1277 x 190 x 60	225	R4861/254DD	2457 x 190 x 60	226	R48611/254DD
Standard reflector – satin-anodised aluminium – EQUILUM® baffles – individually switchable up and down lights – RAL9006 white aluminium							
	T5 – ø 16mm (3000K + 6500K)						
60°	1 + 2 x 28W	1345 x 250 x 60	227	R4901/328DDX2			
Options and accessories p. 83							
Suspended luminaires – straight line mounting							
through wiring (5 x 1,5 mm ²): included as standard							
Standard reflector – satin-anodised aluminium – EQUILUM® baffles							
	T5 – ø 16mm (3000K + 6500K)						
65°	1 + 1 x 49W	1529 x 190 x 60	228	R4863/249DD	1480 x 190 x 60	228	R4865/249DD
	1 + 1 x 54W	1229 x 190 x 60	228	R4863/254DD	1180 x 190 x 60	228	R4865/254DD
Options and accessories p. 83							
Suspended luminaires – angular line mounting							
through wiring (5 x 1,5 mm ²): included as standard							
Standard reflector – satin-anodised aluminium – EQUILUM® baffles							
	T5 – ø 16mm (3000K + 6500K)						
65°	1 + 1 x 49W	1529 x 190 x 60	229	R4867/249DD	1480 x 190 x 60	229	R4869/249DD
	1 + 1 x 54W	1229 x 190 x 60	229	R4867/254DD	1180 x 190 x 60	229	R4869/254DD
Options and accessories p. 83							

¹ ordercode + X1: luminaire out of RAL9003-white / ordercode + X2: luminaire out of RAL9006-white aluminium